

## Technical data

• Type	3/8" tufted non filled synthetic grass carpet, straight stitch pattern	
• Pile content	100% Ten Cate Grass, polyethylene, PP rootzone - monofilament U.V.stabilized, 12,400 Dtex	
• Primary backing	Polypropylene, U.V.-stabilised, Double layers, total weight 240 g/sq.m.	
• Secondary backing	SBR latex, approx. 900 g/sq.m. with 4 mm. perforation holes	
• Pile height	± 40 mm	+/- 5%
• Total thickness	± 42	+/- 5%
• Stitch rate per 10 cm (width)	± 10.5	
• Stitch rate per 10 cm (length)	± 15	+/- 1%
• Number of tufts/m <sup>2</sup>	± 15,750	+/- 5%
• Face weight	± 1,760 g/sq.m.	+/- 10%
• Weight primary backing	± 240 g/sq.m.	+/- 10%
• Weight secondary backing	± 900 g/sq.m.	+/- 10%
• Total weight	± 2,900 g/sq.m.	+/- 10%
• Roll width	200 cm. or 400 cm.	+/- 2 cm
• Roll length	As required	
• Tuft bind	± 40 Newton	
• Water permeability	± 60 ltr/sq.m./min (unfilled)	
• Colour fastness	Xenon test : blue-scale >7, grey-scale >4	

## Colour

- Four colours.

## Installation method

- Loose laid on a bound sub base or shock pad, glued seams.

## Infill (recommended)

- 10 mm. of sand (80% round), size of granules 0.3 - 0.8 mm., app. 17 kg/sq.m.

## Product application

- Landscape & Lawns, Parks & Recreation.

100/173 Moo 10, Subboonchai 17, Srinakarin Rd., Bangmuang, Muang, Samutprakarn 10270

Tel : (662) 703-1557-9 Fax : (662) 703-1617

www.turfthai.com